

# From CGI to mod\_perl 2.0, Fast!

Philippe M. Chiasson  
gozer@ectoplasm.org



# Fast!

```
$> wget http://perl.apache.org/download/mod_perl-2.0-current.tar.gz
$> tar zxvf mod_perl-2.0-current.tar.gz
[...]
$> cd mod_perl-2.0.*/
$> perl Makefile.PL MP_APXS=`which apxs`
Configuring Apache/2.0.52 mod_perl2/2.0.2 Perl/v5.8.6
[...]
$> make
cd "src/modules/perl" && make
[...]
$> make test

$> make install
$> perl -pi -e's/cgi_module/perl_module/g' `apxs -q SYSCONFDIR`/httpd.conf
$> perl -pi -e's/mod_cgi/mod_perl/g' `apxs -q SYSCONFDIR`/httpd.conf
$> perl -pi -e's/cgi-script/perl-script/g' `apxs -q SYSCONFDIR`/httpd.conf
$> `apxs -q SBINDIR`/apachectl configtest
Syntax OK
$> `apxs -q SBINDIR`/apachectl restart
```

# Faster!

```
$> wget -O- http://gozer.ectoplasm.org/talks/ApacheCon/2005/US/mod\_perl-2.0-cgi-fast/fast.sh | sh -x
```

# Better!

```
$> yum install mod_perl
```

```
$> apt-get mod_perl
```

```
$> fink install mod_perl
```

```
$> pkg_add -r mod_perl
```

```
$> emerge mod_perl
```

# Thank You!

# Do we still have time?

Let's get serious!

# You have

- Apache 2.x
- mod\_cgi
- A bunch of Perl CGI scripts
- A working web site
- A good job



# Common Gateway Interface

- CGI is simple
- CGI is easy
- CGI just works

# How about mod\_perl?

- mod\_perl is simple
- mod\_perl is easy
- mod\_perl just works

# How about mod\_perl?

- mod\_perl is simple
- mod\_perl is easy
- mod\_perl just works **BETTER**

# How about mod\_perl?

- mod\_perl is simple
- mod\_perl is easy
- mod\_perl just works **FASTER**

# How about mod\_perl?

- mod\_perl is simple
- mod\_perl is easy
- mod\_perl just works EASIERer

# But why switch?

- CPU cycles
- Memory
- Servers
- \$\$\$
- Apache::\* module on CPAN

# The CGI model

- Forking
- Startup
- Teardown

# The CGI model

- httpd fork()s
- httpd exec(/var/www/cgi-bin/myscript.pl)
- OS find #!/usr/bin/perl in /var/www/cgi-bin/myscript.pl
- OS fork()s
- OS exec()s /usr/bin/perl
- Perl opens, initializes and parses myscript.pl
- Perl runs the script



# The CGI model

2x fork()  
2x exec()  
Perl startup  
Perl shutdown

# EXPENSIVE

# The mod\_perl model

- Embedded Perl
- One time startup
- One time teardown

# The mod\_perl model

- Perl locates the correct subroutine to invoke
- Perl calls it

CHEAP<sub>er</sub>

# Getting there from here

# mod\_cgi setup

```
LoadModule cgi_module libexec/mod_cgi.so
```

```
ScriptAlias /cgi-bin/ /var/www/cgi-bin
```

# mod\_cgi setup

## ScriptAlias is just shorthand

```
LoadModule cgi_module libexec/mod_cgi.so
```

```
Alias /cgi-bin /var/www/cgi-bin
```

```
<Location /cgi-bin>
```

```
    SetHandler cgi-script
```

```
    Option +ExecCGI
```

```
</Location>
```

# mod\_cgi setup

`/var/www/cgi-bin/hello.pl`

```
#!/usr/bin/perl

use CGI;

my $q = new CGI;

print $q->header('text/html');

print <<"EOF";
<html><body>
<h1>Hello world!</h1>
<pre>
GATEWAY_INTERFACE: $ENV{GATEWAY_INTERFACE}
MOD_PERL: $ENV{MOD_PERL}
</pre>
</body></html>
EOF
```

# mod\_cgi setup





# How fast is that ?

- Apache Bench (ab)
- Nice benchmarking tool
- Will work for us nicely
- Comes with Apache

# How fast is that ?

```
$> ab -c1 -n50 http://localhost:8529/cgi-bin/hello.pl  
Benchmarking 127.0.0.1 (be patient).....done  
Requests per second:      5.57 [# /sec] (mean)  
Time per request:        179.448 [ms] (mean)  
Transfer rate:           1.67 [Kbytes/sec] received
```

# mod\_perl time

```
$> wget http://perl.apache.org/download/mod_perl-2.0-current.tar.gz
$> tar zxvf mod_perl-2.0-current.tar.gz
[...]
$> cd mod_perl-2.0.*/
$> perl Makefile.PL MP_APXS=`which apxs`
Configuring Apache/2.0.52 mod_perl2/2.0.x Perl/v5.8.6
[...]
$> make
cd "src/modules/perl" && make
[...]
$> make test

$> make install
$> perl -pi -e's/cgi_module/perl_module/g' `apxs -q SYSCONFDIR`/httpd.conf
$> perl -pi -e's/mod_cgi/mod_perl/g' `apxs -q SYSCONFDIR`/httpd.conf
$> perl -pi -e's/cgi-script/perl-script/g' `apxs -q SYSCONFDIR`/httpd.conf
$> `apxs -q SBINDIR`/apachectl configtest
Syntax OK
$> `apxs -q SBINDIR`/apachectl restart
```

# mod\_perl time

## Download & unpack

```
$> wget http://perl.apache.org/download/mod\_perl-2.0-current.tar.gz
$> tar zxvf mod_perl-2.0-current.tar.gz
[... ]
$> cd mod_perl-2.0.* /
```

# mod\_perl time

## Configure

```
$> /usr/bin/perl Makefile.PL MP_APXS=/usr/sbin/apxs  
Configuring Apache/2.0.52 mod_perl2/2.0.x Perl/v5.8.6  
[...]
```

# mod\_perl time

Build, test, install

```
$> make  
$> make test  
$> make install
```

# mod\_perl time

Check your distro!

mod\_perl is supported by lots of them

# mod\_perl time

## httpd.conf

```
LoadModule cgi_module modules/mod_cgi.so  
LoadModule perl_module modules/mod_perl.so
```

```
Alias /cgi-bin /var/www/cgi-bin  
Alias /perlrun /var/www/cgi-bin
```

```
<Location /cgi-bin>  
  SetHandler cgi-script  
  Option +ExecCGI  
</Location>  
<Location /perlrun>  
  SetHandler perl-script  
  Option +ExecCGI  
  PerlHandler ModPerl::PerlRun  
</Location>
```



# mod\_perl time

- SetHandler
- PerlHandler
- ModPerl::PerlRun

# mod\_perl time

```
$> apachectl restart  
[notice] Apache/2.0.52 (Unix) mod_perl/2.0.x Perl/v5.8.7 configured
```

# mod\_perl time



# it works!

- `$ENV{MOD_PERL} = "mod_perl/2.0.x";`

# How fast is THAT ?

```
$> ab -c1 -n50 http://localhost:8529/perlrun/hello.pl  
Benchmarking 127.0.0.1 (be patient).....done  
Requests per second:      83.15 [# /sec] (mean)  
Time per request:        12.027 [ms] (mean)  
Transfer rate:           26.61 [Kbytes/sec] received
```

# How fast is THAT ?

## mod\_cgi

```
$> ab -c1 -n50 http://localhost:8529/cgi-bin/hello.pl  
Benchmarking 127.0.0.1 (be patient).....done  
Requests per second:      5.57 [#/sec] (mean)  
Time per request:        179.448 [ms] (mean)  
Transfer rate:           1.67 [Kbytes/sec] received
```

## ModPerl::PerlRun

```
$> ab -c1 -n50 http://localhost:8529/perlrun/hello.pl  
Benchmarking 127.0.0.1 (be patient).....done  
Requests per second:      83.15 [#/sec] (mean)  
Time per request:        12.027 [ms] (mean)  
Transfer rate:           26.61 [Kbytes/sec] received
```

# How fast is THAT ?

## mod\_cgi

```
$> ab -c1 -n50 http://localhost:8529/cgi-bin/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      5.57 [#/sec] (mean)
Time per request:        179.448 [ms] (mean)
Transfer rate:           1.67 [Kbytes/sec] received
```

## ModPerl::PerlRun

```
$> ab -c1 -n50 http://localhost:8529/perlrun/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      15x(mod_cgi) [#/sec] (mean)
Time per request:        15x(mod_cgi) [ms] (mean)
Transfer rate:           16x(mod_cgi) [Kbytes/sec] received
```

# ModPerl::PerlRun

- mod\_perl's bundled module
- closest CGI emulation available



# ModPerl::PerlRun

On every request for the script:

- Found
- Loaded
- Parsed
- BEGIN {
- Executed
- END }
- Destroyed


# ModPerl::Registry

## httpd.conf

```
Alias /cgi-bin /var/www/cgi-bin
Alias /perlrun /var/www/cgi-bin
Alias /registry /var/www/cgi-bin
```

```
<Location /cgi-bin>
  SetHandler cgi-script
  Option +ExecCGI
</Location>
<Location /perlrun>
  SetHandler perl-script
  Option +ExecCGI
  PerlHandler ModPerl::PerlRun
</Location>
<Location /perlrun>
  SetHandler perl-script
  Option +ExecCGI
  PerlHandler ModPerl::Registry
</Location>
```

# ModPerl::Registry



# How fast is THAT ?

```
$> ab -c1 -n50 http://localhost:8529/registry/hello.pl  
Benchmarking 127.0.0.1 (be patient).....done  
Requests per second:    156.37 [# /sec] (mean)  
Time per request:      6.395 [ms] (mean)  
Transfer rate:         50.04 [Kbytes/sec] received
```

# How fast is THAT ?

## mod\_cgi

```
$> ab -c1 -n50 http://localhost:8529/cgi-bin/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      5.57 [# /sec] (mean)
Time per request:        179.448 [ms] (mean)
Transfer rate:           1.67 [Kbytes/sec] received
```

## ModPerl::PerlRun

```
$> ab -c1 -n50 http://localhost:8529/perlrun/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      83.15 [# /sec] (mean)
Time per request:        12.027 [ms] (mean)
Transfer rate:           26.61 [Kbytes/sec] received
```

## ModPerl::Registry

```
$> ab -c1 -n50 http://localhost:8529/registry/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      156.37 [# /sec] (mean)
Time per request:        6.395 [ms] (mean)
Transfer rate:           50.04 [Kbytes/sec] received
```

# How fast is THAT ?

## mod\_cgi

```
$> ab -c1 -n50 http://localhost:8529/cgi-bin/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      5.57 [#/sec] (mean)
Time per request:        179.448 [ms] (mean)
Transfer rate:           1.67 [Kbytes/sec] received
```

## ModPerl::PerlRun

```
$> ab -c1 -n50 http://localhost:8529/perlrun/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      15x(mod_cgi) [#/sec] (mean)
Time per request:        15x(mod_cgi) [ms] (mean)
Transfer rate:           16x(mod_cgi) [Kbytes/sec] received
```

## ModPerl::Registry

```
$> ab -c1 -n50 http://localhost:8529/registry/hello.pl
Benchmarking 127.0.0.1 (be patient).....done
Requests per second:      28x(mod_cgi) [#/sec] (mean)
Time per request:        28x(mod_cgi) [ms] (mean)
Transfer rate:           30x(mod_cgi) [Kbytes/sec] received
```

# ModPerl::Registry

- mod\_perl's bundled module
- Faster, but CGI emulation laking

# ModPerl::Registry

On every request for the script:

- Load from file if:
  - Not found in cache
  - Cache entry is older than the file
- BEGIN {
- Executed
- END }



# ModPerl::(PerlRun|Registry)

- Try ModPerl::Registry first
  - faster
  - might break some CGIs
- Try ModPerl::PerlRun after
  - slower
  - might break some CGIs

# ModPerl::(PerlRun|Registry)

- Simple Perl modules
- Designed to run perl scripts from mod\_perl pretending it's a CGI
- Derives from ModPerl::RegistryCooker
- New ones can be made in a pinch

```

package ModPerl::PerlRun;
use base qw(ModPerl::RegistryCooker);

sub handler : method {
    my $class = (@_ >= 2) ? shift : __PACKAGE__;
    my $r = shift;
    return $class->new($r)->default_handler();
}

my $parent = 'ModPerl::RegistryCooker';
my %aliases = (
    new          => 'new',
    init         => 'init',
    default_handler => 'default_handler',
    run          => 'run',
    can_compile  => 'can_compile',
    make_namespace => 'make_namespace',
    namespace_root => 'namespace_root',
    namespace_from => 'namespace_from_filename',
    is_cached    => 'FALSE',
    should_compile => 'TRUE',
    flush_namespace => 'flush_namespace_normal',
    cache_table  => 'cache_table_common',
    cache_it     => 'NOP',
    read_script  => 'read_script',
    shebang_to_perl => 'shebang_to_perl',
    get_script_name => 'get_script_name',
    chdir_file   => 'NOP',
    get_mark_line => 'get_mark_line',
    compile      => 'compile',
    error_check  => 'error_check',
    should_reset_inc_hash => 'TRUE',
    strip_end_data_segment => 'strip_end_data_segment',
    convert_script_to_compiled_handler =>
'convert_script_to_compiled_handler',
);

$aliases{$_} = $parent . "::" . $aliases{$_} for keys %aliases;
__PACKAGE__->install_aliases(\%aliases);

```

# CGI emulation

- It's an emulation
- It ain't the real thing
- things can go wonky

# I remember

```
#!/usr/bin/perl

use CGI;

my $q = new CGI;

print $q->header('text/plain');

$count++;
```

```
print <<"EOF";
counted $count
EOF
```

# I remember

```
#!/usr/bin/perl
```

```
use CGI;
```

```
my $q = new CGI;
```

```
print $q->header('text/plain');
```

```
$counter++;
```

```
print <<"EOF";  
counted $counter  
EOF
```

```
$> GET http://localhost:8529/cgi-bin/count.pl  
counted 1
```

```
$> GET http://localhost:8529/cgi-bin/count.pl  
counted 1
```

```
$> GET http://localhost:8529/cgi-bin/count.pl  
counted 1
```

# I remember

```
#!/usr/bin/perl
```

```
use CGI;
```

```
my $q = new CGI;
```

```
print $q->header('text/plain');
```

```
$counter++;
```

```
print <<"EOF";  
counted $counter  
EOF
```

```
$> GET http://localhost:8529/registry/count.pl
```

```
counted 1
```

```
$> GET http://localhost:8529/registry/count.pl
```

```
counted 2
```

```
$> GET http://localhost:8529registry/count.pl
```

```
counted 3
```

```
$> GET http://localhost:8529registry/count.pl
```

```
counted 1
```

```
$> GET http://localhost:8529registry/count.pl
```

```
counted 4
```

# That can't be right?

```
#!/usr/bin/perl

use CGI;

my $q = new CGI;

print $q->header('text/plain');

$counter++;

print <<"EOF";
counted $counter
EOF
```



# That can't be right?

- Code is cached
- Perl sticks around
- Great for speed
- Globals are suddenly **VERY GLOBAL**

# That can't be right?

```
#!/usr/bin/perl

use CGI;

my $q = new CGI;

print $q->header('text/plain');

$counter++;

print <<"EOF";
counted $counter
EOF
```

# That can't be right?

```
#!/usr/bin/perl

use CGI;

my $q = new CGI;

print $q->header('text/plain');

$main::counter++;    # GLOBAL!

print <<"EOF";
counted $counter
EOF
```

# That can be right!

```
#!/usr/bin/perl

use CGI;

my $counter;
my $q = new CGI;

print $q->header('text/plain');

$counter++;

print <<"EOF";
counted $counter
EOF
```

# Globals will stick

- Globals will stick around
- Use my
  - Try `ModPerl::PerlRun`

# CGI emulation

- It's an emulation
- It ain't the real thing
- things can go wonky

# I still remember

```
#!/usr/bin/perl

use CGI;
use strict;
use warnings;

my $q = new CGI;
my $counter;

print $q->header('text/plain');

counter_up();

sub counter_up {
    $counter++;
    print "Counter: $counter\n";
}
```

```
$> GET http://localhost:8529/registry/count.pl
Counter: 1
$> GET http://localhost:8529/registry/count.pl
Counter: 2
$> GET http://localhost:8529/registry/count.pl
Counter: 3
$> GET http://localhost:8529/registry/count.pl
Counter: 1
$> GET http://localhost:8529/registry/count.pl
Counter: 4
```

# But, what the..?

- I used my so it's not a global...
- To Perl, all code lives in subroutines
- `mod_perl` turns scripts into subroutines
- subroutines can create closures



# subification<sup>\*</sup>

```
#!/usr/bin/perl

use CGI;
use strict;
use warnings;

my $q = new CGI;
my $counter;

print $q->header('text/plain');

counter_up();

sub counter_up {
    $counter++;
    print "Counter: $counter\n";
}
```

\* the process of making a subroutine, obviously

# subification<sup>\*</sup>


- subroutine needs a name
- filepath is a convenient naming

\* the process of making a subroutine, obviously

# subification\*

/var/www/cgi-bin/hello.pl

`ModPerl::ROOT::ModPerl::Registry::var_www_cgi_2dbin_hello_2ep1::handler`



\* the process of making a subroutine, obviously

# subification\*

sub

```
ModPerl::ROOT::ModPerl::Registry::var_www_cgi_2dbin_count_2epl::handler {  
package ModPerl::ROOT::ModPerl::Registry::var_www_cgi_2dbin_count_2epl;  
no warnings;  
local $0 = '/var/www/cgi-bin/count.pl';
```

```
use CGI;  
use strict;  
use warnings;
```

```
my $q = new CGI;  
my $counter;
```

```
print $q->header('text/plain');
```

```
counter_up();
```

```
sub counter_up {  
    $counter++;  
    print "Counter: $counter\n";  
}
```

```
}
```

\* the process of making a subroutine, obviously

# closures

- Closures are a Perl feature
- Come to be when creating subs
- Normally not an issue
- `mod_perl` can create some without telling you
- `man perlref` for more

# I still remember

```
#!/usr/bin/perl

use CGI;
use strict;
use warnings;

my $q = new CGI;
my $counter;

print $q->header('text/plain');

counter_up();

sub counter_up {
    $counter++;    # GLOBAL
    print "Counter: $counter\n";
}
```

2 warning signs to look for:  
globals

**error\_log:**

Variable "\$counter" will not stay  
shared at /var/www/cgi-bin/  
count.pl

# I still remember

```
#!/usr/bin/perl

use CGI;
use strict;
use warnings;

my $q = new CGI;
my $counter;

print $q->header('text/plain');

counter_up($counter);

sub counter_up {
    my $counter = shift;
    $counter++;    # GLOBAL
    print "Counter: $counter\n";
}
```

Just remember that  
globals in general are to  
watch out for

# Good advice

- use strict;
- use warnings;
- avoid globals
- look for hints in your error\_log file



# CGI emulation

- It's an emulation
- It ain't the real thing
- things can go wonky

# I used to work

```
#!/usr/bin/perl

use CGI;
use strict;
use warnings;

require "countlib.pl";

my $q = new CGI;

print $q->header('text/plain');

counter_up();
```

```
#countlib.pl

use strict;
my $counter = 0;

sub counter_up {
    $counter++;
    print "Counter: $counter\n";
}
```

# I used to work



## error\_log:

```
[Sun Oct 23 21:37:44 2005] [error] Can't locate countlib.pl in @INC (@INC contains: [...]) at /var/www/cgi-bin/hello.pl line 7.\n
```

# I used to work

```
#!/usr/bin/perl
```

```
use CGI;  
use strict;  
use warnings;  
use Cwd;
```

```
my $q = new CGI;
```

```
print $q->header('text/plain');  
print "Cwd: ", cwd(), "\n";
```

```
$> GET http://localhost:8529/cgi-bin/cwd.pl  
Cwd: /var/www/cgi-bin  
$> GET http://localhost:8529/registry/cwd.pl  
Cwd: /
```

# I used to work

- `mod_cgi`
  - `fork()`s
  - `chdir()`s to the script's directory

# Cwd

- mod\_perl
  - doesn't fork()
  - doesn't chdir()s
  - could chdir()s

# Cwd

- Cwd() is a process property
- Apache threaded MPMs
- chdir() isn't thread-safe
- mod\_perl doesn't try to break things

# Cwd

- You can fix your scripts
  - use `lib()`;
  - require “/fully/qualified/lib/path.pl”;



# Cwd

- If your MPM is Prefork:
  - `ModPerl::RegistryPrefork`
  - `ModPerl::PerlRunPrefork`

# It ain't magical!

- use `strict/warnings`
- Think about globals
- watch the `error_log`

# More info

- *mod\_perl User's mailing-list*
  - <http://perl.apache.org/maillist/modperl.html>
  - [<modperl@perl.apache.org>](mailto:modperl@perl.apache.org)
- *mod\_perl Developer's Cookbook*
  - <http://www.modperlcookbook.org/>
- **Practical mod\_perl**
  - <http://www.modperlbook.org/>
- **mod\_perl at the ASF**
  - <http://perl.apache.org/>

# Thank You!

Slides and bonus material:

<http://gozer.ectoplasm.org/talk/>